

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the reissue application:

Listing of Claims:

1. (previously presented) A convertible rongeur comprising
a front handle piece pivotably attached to a pivot point in a bottom shaft piece having
a tip portion and a handle portion,
engagement means whereby said front handle piece is engaged with a top shaft
cutting piece so as to slideably advance and retract said top shaft cutting piece
relative to the tip portion of said bottom shaft piece when said front handle piece
is compressed relative to said handle portion of said bottom shaft piece,
spring means to resist said compression and hold said front handle piece apart from
said handle portion of said bottom shaft piece,
wherein release means permits said top shaft cutting piece to open from the front, to
allow access for cleaning,
and wherein said top shaft cutting piece, when so opened, remains attached by
attachment means to the body of the rongeur, so as to retain all parts of said
rongeur in one attached unit at all times.
2. (amended) [A]The rongeur as in claim 1, wherein said engagement means comprises
a driving slot in the top end of said front handle piece that engages a driving pin in
said top shaft.
3. (amended) [A]The rongeur as in claim 2, wherein said release means comprises a
retractable mounting for said front handle piece, which when biased so as to retract
said front handle piece, permits said driving pin to unseat from said driving slot and
slide over said top end of said front handle piece.
4. (amended) [A]The rongeur as in claim 3, wherein said front handle can also be
retracted so that said driving pin may slide back over said top end of said front handle
piece so as to reseat in said driving slot.

5. (amended) [A]The rongeur as in claim 1, wherein said attachment means comprises a metal link pivotally attached at one end thereof to the rear portion of said top shaft cutting piece [“and a central point on the top side” to]and at the other end thereof to a central point between the tip and handle portions of said bottom shaft piece.
6. (amended) [A]The rongeur as in claims 3 or 4, wherein said driving slot is positioned so as to slant rearward at the top at an angle of approximately 14 degrees from the vertical, and wherein said front handle piece comprises a radius and a ramp to the rear of said slot so as to facilitate the sliding of said driving pin over said top end of said front handle piece.
7. (amended) [A]The rongeur as in claim 3, wherein said spring means comprise two elongated spring pieces each having a top and bottom end, the bottom ends of which are attached, respectively, to said front handle piece and said handle portion of said bottom shaft piece, and the top ends of which are rotatably or hingably joined together in a manner such that said springs do not readily detach from each other when said front handle piece is loosened or retracted.
8. (twice amended) A convertible rongeur comprising
a front handle piece;
a bottom shaft piece moveably attached to said front handle piece, said bottom shaft piece having a tip portion and a handle portion and a longitudinal axis from said handle portion to said tip portion, said front handle piece being compressed toward said handle portion of said bottom shaft piece to operate said rongeur; and
a top shaft cutting piece slideably engaged, along said longitudinal axis, with said tip portion of said bottom shaft piece, said top shaft cutting piece being
disengageable with said tip portion of said bottom shaft piece;
wherein, when said top shaft cutting piece is disengaged from said tip portion of said bottom shaft piece, said top shaft cutting piece remains attached to said rongeur so as to retain all parts of said rongeur in one attached unit.